



### Aluminium AluK BSF70 HI Single/French Door Form

Direct Trade (Yorkshire) Ltd Unit 3 Sandall Carr Industrial Estate, Sandall Carr Road, Kirk Sandall, Doncaster, DN3 1QL.

Tel: 01302 880066 Fax: 01302 887070 Email: quotes@directtradeltd.co.uk / orders@directtradeltd.co.uk

Date of Order: \_\_\_\_\_ Quote  Order

Reference \_\_\_\_\_ Date Required \_\_\_\_\_

Company Name \_\_\_\_\_ Delivery Address \_\_\_\_\_

Address \_\_\_\_\_

Postcode \_\_\_\_\_ Postcode \_\_\_\_\_



Telephone \_\_\_\_\_ Fax \_\_\_\_\_ Email \_\_\_\_\_

Sign: \_\_\_\_\_ Print: \_\_\_\_\_


Overall Width (mm) \_\_\_\_\_ Overall Height (mm) \_\_\_\_\_ Open In  Open Out

**Including Cills & Add Ons**

Single Door



French Door



Please indicate Master Door - Fingerbolt will be applied to the Slave

All viewed from the outside

**Size Limitations: Each panel must be no larger than 1200mm wide & 100kg in weight, no smaller than 550mm with a Maximum height of up to 2400mm, subject to wind load deflection (No calculations made unless specified)**

54mm Rebated Threshold  34mm Non Weather Rated Threshold  22mm Non Thermal Room Divider

**Standard Single Colour Options:**

RAL 9005 Black Matt  RAL 7016 Anthracite Grey Matt  RAL 9910 White High Gloss

**Standard Dual Colour:**

RAL 7016 Anthracite Grey Matt Externally / RAL 9910 White High Gloss Internally

RAL Internally: \_\_\_\_\_ / Colour: \_\_\_\_\_ High Gloss  Semi Gloss  Matt

RAL Externally: \_\_\_\_\_ / Colour: \_\_\_\_\_ High Gloss  Semi Gloss  Matt

Marine Guarantee Required Please Tick  \*For Marine Environment applications, please refer to disclaimer at foot of page.

**Any of the above will incur an additional set-up cost and extended lead time**

**Cill:** No Cill  95mm  150mm  177mm  190mm  Overall Cill Size: \_\_\_\_\_ mm (Cut to Size as Standard)

**Drainage:** Concealed  Face  None

**Traffic Door Handle:** White  Black  Silver  Chrome  (Hinges and Associated Hardware to be Black as Standard)

**24mm Square Bead** - Glazed Yes  No  (4/16/4 Clr Optitherm S1 + Tough / Optifloat Tough Black Warmedge Spacer)

**36mm Chamfered Bead** - Glazed Yes  No  (4/12/4/12/4 Clr Tough/ Ecoplus Tough/ Ecoplus Tough Black Warmedge Spacer)

20mm Extender  40mm Extender  Trickle Vent  Qty \_\_\_\_\_ (4000m<sup>2</sup> trickle vents through 40mm to the head)  
Left / Right / Top Left / Right / Top

**Additional Requirements:**

Please Note: We cannot guarantee any product installed within 50 metres of the coast, source of pollution or 2 metres from a swimming pool against deterioration of profile or hardware. Any product fitted within 5000 metres of a hostile environment a recommended cleaning regime must be adhered to and recorded (please consult product guide) - Additional costs may be incurred, please advise on the environment if appropriate.

All frames are non-load bearing.

34mm and 22mm Low Threshold are not weather rated.



### Aluminium AluK BSF70 HI Single/French Door Form

Direct Trade (Yorkshire) Ltd Unit 3 Sandall Carr Industrial Estate, Sandall Carr Road, Kirk Sandall, Doncaster, DN3 1QL.

Tel: 01302 880066 Fax: 01302 887070 Email: quotes@directtradeltd.co.uk / orders@directtradeltd.co.uk

Date of Order: \_\_\_\_\_ Quote  Order

Reference \_\_\_\_\_ Date Required \_\_\_\_\_

Company Name \_\_\_\_\_ Delivery Address \_\_\_\_\_

Address \_\_\_\_\_

Postcode \_\_\_\_\_ Postcode \_\_\_\_\_



Telephone \_\_\_\_\_ Fax \_\_\_\_\_ Email \_\_\_\_\_

Sign: \_\_\_\_\_ Print: \_\_\_\_\_


Overall Width (mm) \_\_\_\_\_ Overall Height (mm) \_\_\_\_\_ Open In  Open Out

Including Cills & Add Ons

Single Door



French Door



Please indicate Master Door - Fingerbolt will be applied to the Slave

All viewed from the outside

**Size Limitations: Each panel must be no larger than 1200mm wide & 100kg in weight, no smaller than 550mm with a Maximum height of up to 2400mm, subject to wind load deflection (No calculations made unless specified)**

54mm Rebated Threshold  34mm Non Weather Rated Threshold  22mm Non Thermal Room Divider

**Standard Single Colour Options:**  
RAL 9005 Black Matt  RAL 7016 Anthracite Grey Matt  RAL 9910 White High Gloss

**Standard Dual Colour:**  
RAL 7016 Anthracite Grey Matt Externally / RAL 9910 White High Gloss Internally

RAL Internally: \_\_\_\_\_ / Colour: \_\_\_\_\_ High Gloss  Semi Gloss  Matt

RAL Externally: \_\_\_\_\_ / Colour: \_\_\_\_\_ High Gloss  Semi Gloss  Matt

Marine Guarantee Required Please Tick  \*For Marine Environment applications, please refer to disclaimer at foot of page.

**Any of the above will incur an additional set-up cost and extended lead time**

**Cill:** No Cill  95mm  150mm  177mm  190mm  Overall Cill Size: \_\_\_\_\_ mm (Cut to Size as Standard)

**Drainage:** Concealed  Face  None

**Traffic Door Handle:** White  Black  Silver  Chrome  (Hinges and Associated Hardware to be Black as Standard)

**24mm Square Bead** - Glazed Yes  No  (4/16/4 Clr Optitherm S1 + Tough / Optifloat Tough Black Warmedge Spacer)

**36mm Chamfered Bead** - Glazed Yes  No  (4/12/4/12/4 Clr Tough/ Ecoplus Tough/ Ecoplus Tough Black Warmedge Spacer)

20mm Extender  40mm Extender  Trickle Vent  Qty \_\_\_\_\_ (4000m<sup>2</sup> trickle vents through 40mm to the head)  
Left / Right / Top Left / Right / Top

**Additional Requirements:**

Please Note: We cannot guarantee any product installed within 50 metres of the coast, source of pollution or 2 metres from a swimming pool against deterioration of profile or hardware. Any product fitted within 5000 metres of a hostile environment a recommended cleaning regime must be adhered to and recorded (please consult product guide) - Additional costs may be incurred, please advise on the environment if appropriate.

All frames are non-load bearing.

34mm and 22mm Low Threshold are not weather rated.

